

Measurement Assurance and Certification Scotland

Operator specific criteria - Saur Glasgow MACS-OP-05

Version 1 October 2017

Introduction

As Scotland's principal environmental regulator, the Scottish Environment Protection Agency (SEPA) is responsible for protecting and improving Scotland's environment.

SEPA issues a range of authorisations designed to control operator activities which could lead to pollution or environmental damage. Compliance with these authorisations is important to ensure that the environment is protected. An operator's compliance is assessed by SEPA from information gathered from observations, sampling and analysis. These activities may be carried out by an operator under self-monitoring arrangements.

SEPA has established Measurement Assurance and Certification Scotland (MACS) to provide a range of performance standards which ensure data provided by self-monitoring operators is robust, and provides stakeholders with confidence that data is reliable.

Where an operator complies with the requirements of MACS, they will be deemed competent to supply self-monitoring data to SEPA.

SEPA requires all operators and associated organisations certified under MACS to be accredited by the United Kingdom Accreditation Service (UKAS) to ISO/IEC 17025.

Please direct questions regarding the MACS certification process to UKAS at:

United Kingdom Accreditation Service 2 Pine Trees Chertsey Lane Staines-upon-Thames TW18 3HR

Tel: 01784 429 000

Email:info@ukas.comWebsite:www.ukas.com

A Performance characteristics

Specific minimum performance characteristics applicable to the MACS certified analyses required of **Saur Glasgow** (Saur) are detailed in Tables A1, A2 and A3 below. These lists must be used in conjunction with the generic method performance characteristics documented in Annex A of performance standard MACS-WAT-01.

| Determinand | Units ⁽¹⁾ | MDL ⁽²⁾ |
|--|------------------------|--------------------|
| Ammoniacal Nitrogen (as N) | mg/L as N | 0.2 |
| Biochemical Oxygen Demand - ATU suppressed (BOD) ⁽³⁾⁽⁴⁾ | mg/L as O ₂ | 2 |
| Chemical Oxygen Demand (COD) ⁽⁴⁾ | mg/L as O ₂ | 15 |
| Chloride | mg/L | 10 |
| рН | pH units | N/A |
| Reactive Phosphorus (as P) | mg/L as P | 0.01 |
| Suspended Solids (105°C) ⁽⁵⁾ | mg/L | 2 |
| Total Nitrogen (as N) | mg/L as N | 0.5 |
| Total Oxidised Nitrogen (as N) | mg/L as N | 0.2 |
| Total Phosphorus (as P) | mg/L as P | 0.05 |

Table A1 – Inorganic determinands (wastewater matrix)

- 1. Units displayed are not necessarily the units that operators will be required to use when reporting selfmonitoring data to SEPA. Units required for reporting purposes will be defined by SEPA in an operator's Annual Monitoring Plan.
- 2. For further detail on Method Detection Limit (MDL) consult MACS-WAT-01, Annex C.
- 3. Standard 5 day analysis, Allylthiourea (ATU) suppressed.
- Includes filtered BOD and/or filtered COD when stated as a monitoring requirement in the operator's Annual Monitoring Plan. Sample filtered through GF/C (1.2 μm) filter paper before analysis and filtrate analysed as per standard test.
- 5. Sample filtered through GF/C (1.2 $\mu m)$ filter paper. Filter dried for 1 hour at 105 °C.

Table A2 – Metal determinands (wastewater matrix)

| Determinand ⁽¹⁾ | Units ⁽²⁾ | MDL ⁽³⁾ |
|----------------------------|----------------------|--------------------|
| Cadmium | µg/L | 0.04 |
| Chromium | µg/L | 0.5 |
| Copper | µg/L | 1.6 |
| Iron | mg/L | 1 |
| Lead | µg/L | 0.3 |
| Mercury | µg/L | 0.014 |
| Zinc | µg/L | 1.9 |

- Determination of total metal determinand is required, unless otherwise stated.
 Units displayed are not necessarily the units that operators will be required to use when reporting self-monitoring data to SEPA. Units required for reporting purposes will be defined by SEPA in an operator's Annual Monitoring Plan.
 For further detail on Method Detection Limit (MDL) consult MACS-WAT-01, Annex C.

Table A3 – Organic determinands (wastewater matrix)

| Determinand | Units ⁽¹⁾ | MDL ⁽²⁾ |
|----------------------------|----------------------|--------------------|
| gamma - HCH ⁽³⁾ | ng/L | 1.5 |

1. Units displayed are not necessarily the units that operators will be required to use when reporting selfmonitoring data to SEPA. Units required for reporting purposes will be defined by SEPA in an operator's Annual Monitoring Plan.

2. For further detail on Method Detection Limit (MDL) consult MACS-WAT-01, Annex C.

3. gamma-hexachlorocyclohexane (Lindane).

B Reporting requirements

B.1 Data transfer

The preferred mechanism for the transfer of data to SEPA from Saur is via a synchronous Oracle web service. However, until this is fully developed and implemented the following interim solution has been put in place:

- An Excel spreadsheet containing all data intended for submission will be constructed and emailed to <u>operator.data@sepa.org.uk</u>.
- As a minimum, the subject line of each submission email **must** contain at least the following standard text: OSM.
- File names will be defined by the operator; however each individual data file **must** be uniquely named.
- Frequency of data transfer will be at the operator's discretion, but **must** adhere with the requirements of MACS-WAT-02.
- Submission of individual data item(s) to SEPA systems may only be performed once, unless the operator is specifically instructed otherwise by SEPA.

B.2 Data specification

B.2.1 Core dataset

All operator data submissions **must** reference each of the 13 attributes listed in the detailed core dataset specification in Table B1 below.

Automated data submission error notifications will be generated by SEPA systems to alert the operator that remedial action and/or resubmission is required when:

- A value for an attribute identified as a mandatory requirement in Table B1 is missing from a data submission.
- The value supplied for an attribute is not a valid value for that attribute.
- The formatting/data type of a submitted attribute is incorrect.
- A delay reason has not been provided when one is expected, e.g. when the sampled date does not match the scheduled sampling date.
- Data item(s) are submitted which are not expected by SEPA.
- Data item(s) submitted by an operator have previously been submitted and accepted into SEPA systems.

B.2.2 Non-analytical determinands

In addition to the analytical determinands listed in Tables A1, A2 and A3 above, an operator's annual monitoring plan (AMP) may include requirements for some or all of the following non-analytical (or observational) determinands:

- Field comments.
- Overflow operating.
- Weather.

NOTE 1: 'Field comments' are optional data return items and will not be listed on an operator's AMP.

The observation of any non-analytical determinand required of an operator at a monitoring site is expected to be performed at the same time as any scheduled sampling event for the analytical determinand(s) required at that monitoring site.

NOTE 2: 'Overflow operating' observations at a monitoring site are identified on an operator's AMP by their own unique location code; and must be reported against that location code.

Specification of the value(s) required to be submitted by an operator when returning data for each non-analytical determinand listed above is detailed in Table B2 below.

Table B1 – Core dataset specification: Excel submissions

| Attribute | Column header | Value | Value: mandatory? | Value: formatting | Notes |
|-------------------------|---------------------------------|--|----------------------|----------------------|---|
| Operator name | <operator></operator> | SAUR | Y | General | Standard value issued by SEPA. |
| | | | | | Verifies the source of a data submission. |
| Location code | <loccode></loccode> | e.g. 6999 | Y | General | In returning data to SEPA the operator must use the 'LOCATION' code identified in their AMP. |
| Scheduled sampling date | <scheddate></scheddate> | e.g. 02/05/16 | Ν | Text | Where the sample is an additional sample and hence does not have an agreed scheduled date, then a value of N/A must be submitted. |
| Sampled date/time | <sampdatetime></sampdatetime> | e.g. 04/08/16 11:08 | Y | Text | |
| Determinand | <determinand></determinand> | e.g. Biochemical Oxygen Demand - ATU suppressed | Y | General | In returning data to SEPA the operator must use the 'DETERMINAND' names identified in their AMP. For further detail on submission of non-analytical determinands see Table B2. |
| Qualifier | <qualifier></qualifier> | < or > | Ν | General | If NULL, use N/A. |
| Value | <value></value> | e.g. 45.6 | Ν | Text | If the result has been cancelled, then a value of N/A must be submitted. |
| Unit | <unit></unit> | e.g. MGL | Y | General | In returning data to SEPA the operator must use the 'UNIT' names identified in their AMP. |
| Accredited | <accred></accred> | T or F | Y | General | 'T' = ISO/IEC 17025 accredited result.'F' = unaccredited result. |
| Subcontracted | <subcontracted></subcontracted> | T or F | Y | General | 'T' = subcontracted result.'F' = in-house result. |

| Attribute | Column header | Valuo | | Value: mandatory? | Value: formatting | Notes |
|-----------------------------|--|---|---|----------------------|----------------------|---|
| | | Value | Associated reason | | Number | If NULL, use N/A. Where provided, the submission must use the ' <i>Value</i> ' listed against the appropriate ' <i>Associated reason</i> '. |
| | | 1 | Sample bottle incorrect | | | |
| | | 2 | Sample bottle incorrectly filled | | | |
| | | 4 | Sample bottle damaged in transit (to lab) | | | |
| | | 5 | Sample contaminated | | | |
| | | 6 | Sample bottle damaged in transit (between labs) | | | |
| | | 7 | Sample bottle stored incorrectly | | | |
| | | 8 | Sample preservation incorrect | | | |
| | | 9 | Sample deterioration | | | |
| Non-conformance reason code | <ncreason> 10 11 12 13 14 15 16</ncreason> | 10 | Sample bottle delivery time target exceeded | | | |
| | | 11 | Determinand analytical time target exceeded at receipt | | | |
| | | 12 | Determinand preparation time target exceeded at receipt | | | |
| | | Sample prep. delayed beyond determinand preparation time target | | | | |
| | | 14 | Sample analysis delayed beyond determinand analytical time target | - | | |
| | | 15 | Sample bottle damaged within analysing laboratory | | | |
| | | 16 | Sampler not accredited | | | |

| Attribute | Column header | Value | | Value: mandatory? | Value: formatting | Notes |
|--------------------|---|---------------------------------------|---|----------------------|---|--|
| | | 17 | Result associated with QC failure | | | |
| | | 18 | Other MACS AQC requirement not met | | | |
| | | Value | Associated reason | | | |
| | | А | No discharge | | | |
| | | В | No access available | | | If NULL, use N/A. |
| | <delayreason> E F G H I</delayreason> | Bottle broken prior to receipt in lab | | Text | If 'Scheduled sampling date' ≠ 'Sampled date' (with time removed) then a delay reason is expected. Where provided, the submission must use the 'Value' listed against the appropriate 'Associated reason'. | |
| Sampling delay | | Autosampler issue | | | | |
| reason code | | Е | Vehicle breakdown | - N | Text | The requirement to supply a delay reason is also applicable to samples collected prior to the agreed scheduled date. |
| | | F | Unexpected staff absence | | | |
| | | G | Adverse weather | | | |
| | | Н | Autosampler empty | | | Data submitted from additional samples must not be supplied with a delay reason applied. |
| | | 1 | Other reason (recorded in field comments) | | | |
| Operator reference | <operatorref></operatorref> | e.g. 334990499 | | Y | Text | Value defined by the operator; to be used by all parties to facilitate discussion when required e.g. where a submission is associated with a concession request, or has issues/errors. It is suggested that this should be either the unique identifier of the result or of the sample. |

| Determinand | Value | | Notes |
|--------------------|--------------------------|-------------------|--|
| Field comments | e.g. Sample coloured red | | Free text field to max. 254 characters. Only to be provided when a comment has been recorded by the sampler. |
| Overflow operating | T or F | | 'T' = overflow is operating. 'F' = overflow not operating. Where no overflow observation is carried out, the protocol detailed in Table B1 for supplying a cancelled 'Value' must be followed. |
| | Value | Description | |
| | 1 | Sunny and hot | |
| | 2 | Sunny and warm | |
| | 3 | Sunny and cold | Submissions must use the ' Value ' listed |
| | 4 | Overcast and warm | against the appropriate ' Description '. |
| | 5 | Overcast and cold | |
| Weather | 6 | Sunny intervals | Where no weather observation is carried |
| | 7 | Fog / mist / haar | out, the protocol detailed in Table B1 for |
| | 8 | Light rain | supplying a cancelled 'Value' must be |
| | 9 | Showers | followed. |
| | 10 | Heavy rain | ··· |
| | 11 | Stormy | ··· |
| | 12 | Snow or sleet | ··· |

Table B2 – Non-analytical determinands: value specification